

連線式柔版印刷機

inline flexo printing machine

特點

Main Feature

- 伺服控制
Servo motor driven
- 12"陶瓷墨輥
12"Anilox roller
- 27"水冷承壓輪
27"Chilled impression roll
- 預套準
Pre-register
- 標記自動套準控制
Mark auto-register control
- 不停機換單
Non-stop job changing
- 遠程技術支持
Connectivity

配件

Accessories

- 清潔系統 Web cleaner
- 表面處理 Corona
- 撕底紙, 黏底紙
Delam Relam
- 儲料系統
Buffer station
- 翻轉架 Turn bar
- 覆膜, 冷燙
laminating and cold foil

技術規格

Technical Specification

材料寬幅 Substrate Width	350mm/450mm/550mm
印刷寬度 Printing Width	340mm/440mm/540mm
齒輪模數 Gear Pitch	3.175mm
印刷長度規格 Printing Repeat	44T-192T 139.7mm — 609.6mm
模切長度規格 Die-cutting Repeat	80T-192T 254mm-609.6mm
最大機器速度 Max Machine Speed	200 Meter/min
送紙軸規格 Unwinder Reel Diameter	1000 mm, Max load 275KG
收紙軸規格 Rewinder Reel Diameter	1000 mm, Max load 275KG
印刷版厚度 Plate thickness	1.14 mm
雙面膠帶厚度 Double side tape	0.38 mm

可印製材料 Product types

- 材料厚度
Substrate Range
12-450 micron
- OPP, BOPP, PVC,
PE, PET, paper,
adhesive paper,
thermal paper,
cardboard,
laminated materials

應用市場 Market

- 貼紙
Self-adhesive
- 收縮膜
shrink sleeve
- 套標
wrap around
- 模內貼
In-mold label
- 軟包裝
Flexible packaging
- 輕卡紙
light carton

